

tesa® 4335

High Performance



Product Information

High-performance masking tape for sharp and clean paint edges

Product Description

tesa® 4335 is a high-performance Washi masking tape optimized for painting masking jobs to create sharp and clean paint edges. It features an ultra-thin Japanese washi paper backing combined with acrylic adhesive, which delivers strong initial tack and adhesion to glass, aluminum, PVC and a wide range of substrates.

This precision masking tape allows residue-free removal. It can be applied indoors for up to 4.5 months and outdoors for up to 6 weeks. Besides, tesa® 4335 can withstand drying at 150°C for 30 minutes, making it a reliable choice for various spray-painting processes.

Product Features

- Ideal for clean, sharp paint lines for precision masking
- Outdoor masking up to 6 weeks
- Indoor masking up to 4.5 months
- Temperature resistance for up to 120 °C for 1 hour or 150 °C for 30 minutes

Application Fields

- Excellent for two-tone paint masking
- Reliable adhesion on smooth and lightly textured surfaces
- Suitable for high-standard painting and lacquering processes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------|-------------------|-------|
| • Backing | Washi paper | • Total thickness | 85 µm |
| • Type of adhesive | acrylic | | |

Product Assortment

- | | | | |
|--------------------|------|---------------------|------------------|
| • Available colors | gold | • Available formats | LOG ROLL TRIMMED |
|--------------------|------|---------------------|------------------|

Properties/Performance Values

- | | | | |
|-----------------------|-----------|-----------------------------------|-----------|
| • Elongation at break | 4 % | • Solvent free | yes |
| • Tensile strength | 38.9 N/cm | • Temperature resistance | very good |
| • Easy to remove | yes | • Temperature resistance (30 min) | 150 °C |
| • Hand tearability | very good | • Temperature resistance (60 min) | 120 °C |
| • Sharp color edge | very good | • UV-resistance | 6 |

For latest information on this product please visit <http://l.tesa.com/?ip=4335>

tesa[®] 4335

High Performance

Product Information

Adhesion to Values

- Steel 1.5 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4335>