

tesapack® EXPRESS

Product Information

57804, 57810

Product Description

tesapack® EXPRESS: Packaging tape for quick, easy sealing. Easy-tear edges for clean tearing—no scissors. Strong hold, UV-resistant, solvent-free, quiet unwind. Available in brown and crystal clear.

Product Features

- tesapack® packing tape with Easy-Tear edges: hand-tearable—no scissors, quick packing
- Strong adhesion, high UV resistance, tear-resistant backing for lasting security
- Ideal for securely sealing shipping boxes, packages, and medium-weight gift packaging
- Easy to use: stick, tear, keep packing—no dispenser or scissors needed
- Unwinds smoothly and quietly—for comfortable packing
- Solvent-free adhesive with strong hold—for long-lasting, UV-resistant bonding
- Available in brown and crystal-clear—fits elegant gifts or classic cartons

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | BOPP and PVC | • Total thickness | 60 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------------|-----------------------|-----------|
| • Elongation at break | 20 % | • Low noise unwinding | yes |
| • Tensile strength | 13 N/cm | • Solvent free | yes |
| • Adhesive strength | High adhesion | • Suitable surfaces | Cardboard |
| • Ageing resistance (UV) | yes | • Tear resistance | yes |
| • Hand tearability | yes | • Unwind force | 3 N/cm |

tesapack[®] EXPRESS

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=57810PPL15A>