

tesafilm® CRYSTAL

Product Information

57947, 57932

Product Description

The tesa® CRYSTAL adhesive tape offers high transparency and strong adhesive power. Ideal for wrapping, fastening, and repairing. It unrolls quietly, is solvent-free, and resistant to aging.

Product Features

- High transparency and strong adhesive power for nearly invisible connections

Versatile use - Ideal for wrapping, securing, repairing, or fixing

Long-lasting adhesion and high resistance to aging with solvent-free adhesive

Quiet and smooth unrolling for pleasant handling in daily use

Compatible with tesa® dispensers for flexible application options

Crystal Clear appearance makes the adhesive tape nearly invisible on many surfaces

Perfect for decorative or creative applications like gift wrapping or crafts

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 50 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|---------------------|------------------|
| • Tensile strength | 27 N/cm | • Suitable surfaces | Paper, Cardboard |
| • Ageing resistance (UV) | yes | • Tear resistance | yes |
| • Hand tearability | no | • Transparency | very good |
| • Low noise unwinding | yes | • Unwind force | 2.5 N/cm |
| • Photocopy neutral | no | • Writable | no |
| • Solvent free | yes | | |

tesafilm® CRYSTAL

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4132A>