

tesafilm® CRYSTAL CLEAR

Product Information

57726, 57418, 57417, 57329, 57766, 57710, 57315, 57316, 57330, 57767, 58260, 57759, 57790, 58244, 58245, 58259

Product Description

The tesafilm® CRYSTAL CLEAR is an exceptionally transparent adhesive tape designed for inconspicuous sticking and wrapping applications. Made from durable Polypropylene, with strong adhesive power and silent unrolling. Solvent-free and resistant to aging.

Product Features

- Highest quality and transparency for nearly invisible adhesion on all surfaces

Ideal for wrapping, securing, and repairing with professional results

Made from durable Polypropylene backing with solvent-free adhesive for strong bonding power

High tear resistance and long-lasting durability for reliable applications

Noiseless unrolling for a pleasant use in the office, school, or home

Compatible with tesafilm® dispensers for versatile uses

Age-resistant quality ensures long-lasting clarity of adhesions

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 55 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|---------------------|------------------|
| • Tensile strength | 31 N/cm | • Suitable surfaces | Paper, Cardboard |
| • Ageing resistance (UV) | yes | • Tear resistance | yes |
| • Hand tearability | no | • Transparency | very good |
| • Low noise unwinding | yes | • Unwind force | 2.7 N/cm |
| • Photocopy neutral | yes | • Writable | no |
| • Solvent free | yes | | |

tesafilm® CRYSTAL CLEAR

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4102A>