

tesafilm® TRANSPARENT

Product Information

57341, 57372, 57406, 57404, 57369, 57342, 57405, 57371, 57345, 57403, 57379, 57401, 57378, 57352, 57402

Product Description

tesafilm® TRANSPARENT: A universal adhesive tape for office, household, and school use. Strong adhesive power, high tear resistance, clear-glossy appearance. Made from durable Polypropylene, solvent-free adhesive.

Product Features

- Universal adhesive tape for office, household, and school with strong adhesion and high tear resistance
- Transparent design for inconspicuous application on many materials and surfaces
- Durable solution thanks to resilient Polypropylene plastic and solvent-free adhesive
- Age-resistant film remains reliably adhesive even after a long time
- Pleasant handling due to noiseless unrolling of the adhesive film
- Compatible with tesafilm® dispensers for comfortable use on a desk or in hand
- Solvent-free adhesive
- Ideal for wrapping, securing, repairing, or decorating in everyday life

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 48 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|---------------------|------------------|
| • Tensile strength | 25 N/cm | • Suitable surfaces | Paper, Cardboard |
| • Ageing resistance (UV) | yes | • Tear resistance | yes |
| • Hand tearability | no | • Transparency | good |
| • Low noise unwinding | yes | • Unwind force | 2.5 N/cm |
| • Photocopy neutral | yes | • Writable | no |
| • Solvent free | yes | | |

tesafilm® TRANSPARENT

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4140A>