

tesafilm® DOUBLE-SIDED

Product Information

57910, 57954, 57911

Product Description

tesafilm® DOUBLE-SIDED: double-sided tape for paper, photos, crafts and decor. Invisible, durable hold on smooth surfaces. Polypropylene backing. For office and home.

Product Features

- tesafilm® DOUBLE-SIDED: transparent, double-sided adhesion - invisible on smooth surfaces

Double-sided tape ideal for mounting photos, crafting, decorating, and securing paper

Clean alternative to liquid glue: reliable, precise application without the mess

Smooth unwind and high aging resistance for long-lasting, strong adhesion

Premium adhesive film: Polypropylen backing - transparent and discreet

Handy dispenser makes handling easy: unwind quickly and place precisely

A mindful choice for creative projects at home and in the office

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 75 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|---------------------|---------------|---------------------|------------------|
| • Tensile strength | 58 N/cm | • Suitable surfaces | Paper, Cardboard |
| • Adhesive strength | High adhesion | • Tear resistance | no |
| • Solvent free | no | • Transparency | medium |

tesafilm® DOUBLE-SIDED

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=57910A>