

By water, by land, and in the air – tesa® solutions in security and protection industries



Security and identification

tesa® 6930x / 694x laser label series offer durable, laser-markable labels that combine the resilience of metal plates with the flexibility of adhesive labels, ideal for security-grade marking applications.

Protection and durability

tesa 5299x polyurethane tapes for safety relevant surfaces to protect against erosion, abrasion, and minor impacts.

tesa® 60973, 60954, and 60955 anti-slip tapes for entrances, floors, gangways, roofs, and platforms with excellent grip and safe footing for heavy-duty use Flame retardant acc. to EN 45545, weather and chemical resistant.

Bonding and assembly

Double-coated tapes: For permanent bonding, vibration dampening, and sealing of dissimilar materials like metals and plastics to ensure reliable lightweight solutions compared to mechanical fasteners e.g. **tesa® ACX^{plus} acrylic foam tape families**.

Electrical and EMI/RFI shielding

tesa® 60318 copper foil tape for EMI shielding in electronic enclosures and tesa® conductive adhesive tapes used in tactical communication equipment to prevent signal interference.

Maintenance and repair

tesa® 4641 non-reflective cloth and duct tapes (cloth waterproof) for heavy-duty, all-purpose field repairs.

tesa® masking tapes (high temp) are used in painting and coating processes on security vehicles and aircraft.

tesa® 53799 security grade duct tape for a wide range of first aid, packaging and sealing applications

Moisture and air barrier: **tesa® 54411 high performance sealer, aluminum tapes and double-sided acrylic foam tapes** prevent ingress of water and contaminants in sensitive equipment.

tesa® Wire Harnessing solutions

tesa solutions to protect sensitive wires from heat, abrasion, moisture, ageing, and noise to enhance vehicle safety and reliability, e.g. **tesa® 51036 PET cloth** for high abrasion protection and **tesa® 68000 Alu-laminated cloth** for radiant heat reflection.

tesa SE
Phone: +49 40 88899 0
tesa.com/company/locations

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.