

tesa® All-Purpose Glue

Product Information

57013, 57007

Product Description

tesa® ALL-PURPOSE GLUE bonds paper, wood, fabric, cork, and leather. It also adheres to metal, glass, porcelain, ceramic, and many plastics. The clear formula resists light, water, and temperature.

Product Features

- tesa® ALL-PURPOSE GLUE bonds paper, wood, fabric, cork, leather to metal, glass, porcelain, ceramic, plastics
- Ideal for quick repairs, model making, and precise crafts at home, office, and workshop
- Innovative 3-in-1 cap: apply dots, draw fine lines, spread over surfaces
- Precise, clean bonding with strong hold thanks to tesa® adhesive technology - dries clear
- Highly resistant to light, cold, heat, and water; long-term resistance to aging

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Type of adhesive acrylic

Properties/Performance Values

- | | | | |
|-----------------------------|---------------|------------------------------------|---|
| • Adhesive strength | High adhesion | • Suitable for children of 3 years | no |
| • Chemical Resistance | no | • of age | |
| • Hazard material | yes | • Suitable surfaces | Glass, Even wood, Steel, Stone, Brick, Acrylic glass, Metal, Paper, Cardboard |
| • Humidity resistance | yes | | |
| • Residue-free removability | no | • Temperature resistance | yes |
| • Solvent free | no | • UV resistant | yes |
| | | • Washable | no |
| | | • Waterproof | no |

tesa® All-Purpose Glue

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=57013A>