

tesa® 60262

50µm double sided grey electrically conductive non-woven tape

tesa® 60262 is a grey double sided electrically conductive self adhesive tape. It consists of an electrically conductive non-woven backing and an electrically conductive acrylic adhesive.

tesa® 60262 features especially:

- Thickness: 50µm
- Excellent electrical conductivity in XYZ-direction even at high temperatures and humidity
- High adhesion level even at harsh environmental conditions
- Excellent conformability and adjustment to uneven surfaces
- Very good die-cuttability

Main Application

- EMC applications, such as grounding
- Electrostatic discharge applications

Technical Data

▪ Backing material	conductive non-woven	▪ Colour of liner	white/blue logo
▪ Color	gray	▪ Thickness of liner	120 µm
▪ Total thickness	50 µm	▪ Release of liner	easy
▪ Type of adhesive	conductive acrylic	▪ Temperature resistance short term	200 °C
▪ Adhesion to Steel (initial)	5.4 N/cm	▪ Contact resistance z-direction (initial)	0.02 Ohm / square inch
▪ Adhesion to Steel (after 14 days)	8.3 N/cm	▪ Surface resistance x-y-direction	0.2 Ohm / square
▪ Type of liner	PE-coated paper		

Properties

- | | | | |
|-----------------------------------|------|-----------------------------------|------|
| ▪ Static shear resistance at 23°C | ●●●● | ▪ Static shear resistance at 40°C | ●●●● |
|-----------------------------------|------|-----------------------------------|------|

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=60262>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.