

tesa® 64250

Flexible transport securing tape

tesa® 64250 combines flexibility with the strength of a tensilised polypropylene backing. Due to its outstanding conformability the product is ideally suited for applications on “3-dimensional” surfaces.

tesa® 64250 can be removed residue- and discoloration-free from a variety of different surfaces.

Main Application

Transport securing of office automation equipment such as printers, scanners, copying machines as well as appliances.

Technical Data

▪ Backing material	MOPP	▪ Adhesion to steel	3 N/cm
▪ Total thickness	79 µm	▪ Elongation at break	30 %
▪ Type of adhesive	acrylic	▪ Tensile strength	100 N/cm

Properties

▪ Residue free removal	yes	▪ No discolouration	yes
------------------------	-----	---------------------	-----

For latest information on this product please visit <http://l.tesa.com/?ip=64250>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.