

## Product Information

200µm d/s high performance removable foam tape

tesa® 66720 is a black double-sided foam tape with a PET reinforcement. The tape is equipped with a special ultra-removable adhesive on one side and a tackified acrylic adhesive on the other side.

tesa® 66720 features:

- Excellent removability on various substrates without residue
- Excellent resistance & stability to demanding environmental conditions
- Waterproof: IPX7

### Main Application

- Car display mounting
- Removable mounting

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	PE foam	• Type of adhesive	tackified acrylic
• Color	black	• Elongation at break	100 %
• Total thickness	200 µm	• Tensile strength	28 N/cm

#### Adhesion to

• Steel (initial)	0.5 N/cm	• Steel (after 14 days)	0.6 N/cm
• Steel (covered side, initial)	7.3 N/cm	• Steel (covered side, after 14 days)	9.5 N/cm
• Glass (initial)	0.5 N/cm	• Glass (after 14 days)	0.6 N/cm
• Glass (covered side, initial)	8.0 N/cm	• Glass (covered side, after 14 days)	8.2 N/cm

#### Properties

• Ageing resistance (UV)	●●●	• Removability after 14 days (23°C)	●●●●
• Humidity resistance	●●●	• Removability after 14 days (85°C, 95% r.h.)	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

#### Additional Information

Liner: PV50 transparent PET-film (50µm; 72g/m<sup>2</sup>)

# tesa® 66720

## Product Information



### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=66720>