




# tesa® 61215

## Product Information



150µm double sided black chemical resistant filmic tape

### Product Features

- Excellent chemical resistance to different polar and non polar chemical
- Excellent shock resistance
- Excellent converting performance due to PET backing
- Double PET liner
- Halogen-freeness
- Skin-compatible (ISO 10993-10:2010; ISO 10993-5:2009)

tesa® 61215 is a double sided self-adhesive tape consisting of a black PET backing and a special chemical resistant adhesive.

### Application Fields

- Cover glass mounting in wearable devices
- Mounting of parts in electronic devices, e.g. keyboard mounting and earphones

### Product Construction

- |                    |                     |                    |          |
|--------------------|---------------------|--------------------|----------|
| • Type of adhesive | specialty           | • Backing material | PET film |
| • Weight of liner  | 72 g/m <sup>2</sup> | • Color            | black    |
| • Total thickness  | 150 µm              |                    |          |

### Product Properties/Performance Values

- |                       |         |                                     |        |
|-----------------------|---------|-------------------------------------|--------|
| • Elongation at break | 50 %    | • Temperature resistance long term  | 70 °C  |
| • Tensile strength    | 20 N/cm | • Temperature resistance short term | 120 °C |

### Adhesion to Values

- |                             |           |                         |           |
|-----------------------------|-----------|-------------------------|-----------|
| • Steel (initial)           | 14.3 N/cm | • Glass (after 14 days) | 15.3 N/cm |
| • PE (initial)              | 6.5 N/cm  | • PE (after 14 days)    | 8 N/cm    |
| • PC (after 14 days)        | 21 N/cm   | • Glass (initial)       | 14.9 N/cm |
| • Aluminium (after 14 days) | 13.7 N/cm | • Aluminium (initial)   | 12.4 N/cm |
| • PC (initial)              | 13.7 N/cm | • Steel (after 14 days) | 15.5 N/cm |



# tesa® 61215

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=61215>