



tesa® 68567

Product Information

100µm double sided transparent removable filmic tape

Product Features

- Excellent permanent removability on various substrates, e.g. PC/ABS/PI/Metal
- High bonding strength and shear resistance of the tackified acrylic adhesive
- Excellent resistance to demanding environmental conditions
- Very good handling performance in converting processes

tesa® 68567 is a double-sided self-adhesive tape consisting of a transparent PET backing with a special removable adhesive on cover side and a tackified acrylic adhesive on open side.

Application Fields

- Removable mounting of FPC
- Sealing support of foam gaskets
- Temporary mounting prior to mechanical fixation

Product Construction

• Type of adhesive	tackified acrylic	• Total thickness	100 µm
• Type of liner	glassine	• Thickness of liner	71 µm
• Color of liner	white/red logo	• Backing material	PET film
• Weight of liner	82 g/m ²	• Color	transparent

Adhesion to Values

• PC (covered side, initial)	0.8 N/cm	• Glass (after 14 days)	11.3 N/cm
• Steel (initial)	8.9 N/cm	• Steel (covered side, after 14 days)	0.7 N/cm
• PC (after 14 days)	14.7 N/cm	• ABS (covered side, initial)	0.9 N/cm
• ABS (initial)	7.6 N/cm	• Glass (initial)	9.5 N/cm
• ABS (after 14 days)	11 N/cm	• PC (covered side, after 14 days)	0.9 N/cm
• ABS (covered side, after 14 days)	0.9 N/cm	• Steel (after 14 days)	11.4 N/cm
• PC (initial)	9.9 N/cm	• Steel (covered side, initial)	0.5 N/cm



tesa[®] 68567

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=68567>