



tesa® 4173 PV2



Product Information

Soft PVC tape for basic bundling in the automotive passenger compartment

Product Features

- Temperature resistance of up to 105°C for 3000h
- Hand-tearable
- Constant unwind force – optimized for manual application
- Flag-resistant
- Resistant to environmental influences
- Ageing-resistant
- Flame-retardant
- Flexible and smooth

tesa® 4173 PV2 is a PVC film tape with an acrylic adhesive for basic bundling of automotive harnesses used in the passenger compartment of vehicles. The tape is convenient to use due to its constant unwind force, flexible backing, and hand-tearability. It is optimized for manual application.

Application Fields

tesa® 4173 PV2 has been particularly developed for efficient bundling of wire harness parts in the automotive passenger compartment.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|--------------------|----------|
| • Type of adhesive | acrylic | • Backing material | PVC film |
| • Total thickness | 126 µm | | |

Product Properties/Performance Values

- | | | | |
|-------------------------------------|-------------------------|--------------------------------------|----------------------------|
| • Elongation at break | 250 % | • Temperature resistance min. | -25 °C |
| • Abrasion resistance (5mm mandrel) | Class A (acc. to LV312) | • Noise damping (decibel) | Class A (acc. to LV312) dB |
| • Temperature resistance (3000h) | 105 °C | • Abrasion resistance (10mm mandrel) | Class A (acc. to LV312) |
| • Tensile strength | 30 N/cm | • Dielectric breakdown voltage | 7000 V |



tesa® 4173 PV2

Product Information

Adhesion to Values

- steel 1.8 N/cm

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 33 m

*Most combinations of width and length are possible

*Further dimensions are available upon request

*Standard core diameter: 38 mm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04173>