

NOPI® Professional 4349



Product Information

Lightly crêped paper masking tape for many types of indoor applications

Our paper masking tape NOPI® 4349 is not only suited for masking during professional paint work but also for general indoor applications such as e.g. attaching, packaging or creating decorative designs. The flat, lightly crêped paper masking tape is fitted with an adhesive made from natural rubber and can be used comfortably. It can be torn off by hand and allows generating sharp paint edges.

Main Application

- Indoor applications
- Attaching lightweight objects
- Decorative designs
- Bundling, packaging, marking

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

- | | | | |
|-----------------------|----------------|-----------------------------------|-----------------------|
| • Total thickness | 110 µm | • Tensile strength | 33 N/cm |
| • Type of adhesive | natural rubber | • Unwind force (roll width > 9mm) | 2.5 N/roll (30 m/min) |
| • Elongation at break | 10 % | | |

Adhesion to

- | | | | |
|---------|----------|------------------|----------|
| • steel | 2.0 N/cm | • rough surfaces | 0.6 N/cm |
|---------|----------|------------------|----------|

Properties

- | | | | |
|--------------------|------|--------------------|-----|
| • Hand tearability | ●●●● | • Sharp color edge | ●●● |
| • Paint anchorage | ●●●● | | |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

NOPI® Professional 4349

Product Information



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04349>