

tesa® Professional

64621



Product Information

Double-sided film adhesive tape for fixating and attaching

The double-sided film adhesive tape tesa® 64621 consists of a PP base fitted with an adhesive made from synthetic rubber. The transparent film tape, which offers a good initial bond, is moisture-resistant and can be used universally to fixate or attach objects. It is a good choice in particular for craftsmen who frequently work at events and are likely to reach a point where quick reactions are needed.

Features

- Fixating and attaching
- Equipping decoration and packaging materials
- Gluing together fabrics, films, paper and plastics

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	PP film	• Color of liner	brown
• Color	transparent	• Thickness of liner	70 µm
• Total thickness	90 µm	• Weight of liner	78 g/m ²
• Type of adhesive	synthetic rubber	• Temperature resistance short term	80 °C
• Type of liner	glassine		

Properties

• Hand tearability	●●●	• Humidity resistance	●●●
• Easy to write on	no	• UV-resistance	●●●
• Paint anchorage	●	• Water resistance	●●
• Temperature resistance short term	80 °C	• Static shear resistance at 23°C	●●
• Temperature resistance long term	40 °C	• Static shear resistance at 40°C	●
• Tack	●●●	• Fluorescent	no
• Abrasion resistance	●●	• Conformability	●●
• Ageing resistance (UV)	●●	• Fogging	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

tesa® Professional 64621

Product Information



tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=64621>