

# tesa® Professional 60952



## Product Information

### Clear anti slip tape

tesa® 60952 is a clear anti slip adhesive tape which is ideally suited for securing areas by invisible means. Many craftsmen find the transparency of the tape useful for such purposes as reducing the slip hazard on high-quality wooden stairs without affecting the stairs' appearance. The anti slip tape is very robust and is resistant to UV light, salt water and cleaning agents. With normal use, it retains its anti slip effect for up to two years. After that, it can be removed easily without leaving a residue.

### Features

- Indoor and outdoor applications
- Applications in which a secure grip underfoot is required
- Black-yellow (tesa® 60951): marking of very slippery surfaces
- Transparent (tesa® 60952): make valuable surfaces such as wooden stairs, for example, safe unobtrusively
- Fluorescent (tesa® 60953): stays bright for a long period for safety and warning purposes in dark rooms

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	PVC film coated with mineral particles	• Tensile strength	30 N/cm
• Total thickness	900 µm	• Thickness of liner	180 µm
• Thickness of tape	720 µm	• Temperature resistance short term	50 °C
• Type of adhesive	acrylic	• Temperature resistance	-5 to +50 °C
• Elongation at break	25 %		

#### Properties

• Hand tearability	●●●	• Resistance to chemicals	●●●
• Easy to remove	no	• Salt water resistant	●●●
• Easy to write on	no	• UV-resistance	●●●
• Suitable for die cutting	yes	• Water resistance	●●●
• Paint anchorage	●	• Fluorescent	yes
• Abrasion resistance	●●●●	• Conformability	●
• Ageing resistance (UV)	●●●	• Fogging	●
• Humidity resistance	●●●	• Removability after 14 days (23°C)	●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

# tesa® Professional 60952

## Product Information



tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=60952>