

tesa® Professional 4621 Multi-purpose tape

Product Information

Multipurpose Tape - Perfect Tear Edge

The green PE fabric tape tesa® 4621 not only impresses with its powerful adhesive performance. The multi-purpose adhesive tape is also easy to unroll, child's play to tear off – lengthwise or across – and thus comfortable to use.

If you want to plaster a wall, it works splendidly as a plastering tape, especially outdoors. It stays in place in all kinds of weather and is resistant to UV and water, allowing you to work with it for up to 8 months. Within 8 weeks, it can be removed without residue. Repositioning isn't a problem, either.

The remarkable characteristics of the fabric adhesive tape are due to the combination of PE (base material), acrylic (adhesive) and polyester (mesh).

Main Application

- Fabric tape for many different applications in- and outdoors
- Perfect tear-off edge: easily torn off by hand (across and lengthwise)
- Residue-free UV: 8 weeks
- · Can be removed without residue within 8 weeks
- · Plastering adhesive tape: ideal to mask and protect during plastering work (interior or exterior wall)
- Further applications: painting a façade, plastering interior or exterior wall, floor marking, bundling cables, secure packaging etc
- Tape composition: base material (PE) with acrylic adhesive reinforced with polyester mesh
- · Clean removability and easy to unwind

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

•	Backing material	PE extruded cloth	•	Temperature resistance max.	95 °C
•	Color	green	•	Temperature resistance (30 min)	95 °C
•	Total thickness	126 μm	•	UV-resistance	8 weeks
•	Type of adhesive	acrylic	•	Mesh	100 count per
•	Elongation at break	22 %			square inch
•	Tensile strength	54 N/cm	•	Unwind force n/cm	1.2 N/cm

Adhesion to

•	steel	3.0 N/cm	•	PE (initial)	1.1 N/cm
•	Glass (initial)	2.7 N/cm			



tesa® Professional 4621 Multi-purpose tape

ves

yes

ves

Product Information

Properties

- Hand tearability Straight tear edges
- Easy to removeEasy to write on
- Suitable for die cutting

- · Certified according to
- Tack
- Abrasion resistance
- Water resistance



Evaluation across relevant tesa® assortment: •••• very good ••• good •• medium • low

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

