

tesa[®] StopWater Tape

BNR 56220

Product Features

- Non-adhesive, white PTFE-tape
- Air & watertight seal
- Deformable and impermeable to water up to 6 bar

Product Description

tesa[®] StopWater Tape is an ultra-thin tape made from PTFE that is perfectly suited to reliably seal screw threads and quickly fix any leaky valve or faucet.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------|-------------------|-------|
| • Type of adhesive | none | • Total thickness | 75 µm |
|--------------------|------|-------------------|-------|

Properties/Performance Values

- | | | | |
|-----------------------------|--------------|--------------------------|--------|
| • Abrasion resistance | no | • Temperature resistance | yes |
| • Area of use | Indoor | • Tensile strength | 9 N/cm |
| • Oil and grease resistance | no | • UV resistant | no |
| • Residue free removal | yes | • Waterproof | yes |
| • Suitable surfaces | Most plastic | • Writable | no |

tesa[®] StopWater Tape

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=NaN>