tesapack® Ultra resistant

Product Information

BNR 45900, 45902

Product Features

- Bundling and palletising * Heavy duty carton sealing * Transport securing * Fixing * End-tabbing

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	glassfibre / PET film	• Total thickness	125 µm
• Type of adhesive	synthetic rubber		

Properties/Performance Values

• Tensile strength	250 N/cm	• Low noise unwinding	no
• Adhesive strength	Very high adhesion	• Solvent free	no
• Ageing resistance (UV)	no	• Suitable surfaces	Cardboard
• Hand tearability	no	• Tear resistance	yes

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?cp=45900