



tesa[®] 4306

Product Information

Premium Painters tape for indoor painting applications

Product Features

- The natural rubber adhesive ensures a good tack and precise coverage.
- tesa[®] 4306 can be removed without any residues.

tesa[®] 4306 consists of slightly creped paper backing. The product is specifically designed for indoor painting applications. The release coated paper backing is impregnated and equipped with a superior natural rubber adhesive.

Application Fields

tesa[®] 4306 is suitable for all kind of painting and masking applications such as:

- masking for straight lines
- masking for slight curves

tesa[®] 4306 is usable for all indoor painting applications on even and rough surfaces for up to 7 days as well as for outdoor applications up to 3 days.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Additional Information

The natural rubber adhesive is generally not UV resistant. tesa[®] 4306 should therefore not be used for more than 3 days outdoors.



tesa® 4306

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04306>