

tesa® 6702

New Bond



Product Information

800µm double-sided acrylic foam tape

tesa® 6702 is double-sided acrylic foam tape with grey color, it utilizes the viscoelasticity of acrylic foam as backing and adhesive at the same time.

Product benefits:

- Sufficient bonding on different substrates
- Good shear resistant
- Temperature resistant

Main Application

Example mounting applications include but are not limited to:

- Reinforcement bar in elevator
- Decoration panel in home appliance

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

| | | | |
|--------------------|----------------|--------------------|----------------------|
| • Backing material | foamed acrylic | • Type of adhesive | pure acrylic |
| • Color | gray | • Type of liner | bi-siliconised paper |
| • Total thickness | 800 µm | | |

Properties

| | | | |
|-------------------------------------|--------|-----------------------------------|------------|
| • Temperature resistance short term | 200 °C | • Static shear resistance at 70°C | >10000 min |
| • Temperature resistance long term | 100 °C | • Static shear resistance at 70°C | ●●● |
| • Static shear resistance | ●●● | | |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

Liner variants:

PV43 White paper with blue logo, d/s release coating (150µm)

tesa® 6702 New Bond

Product Information



tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=06702>