

# tesa® 6700

## New Bond



### Product Information

400µm double-sided acrylic foam tape

tesa® 6700 is double-sided acrylic foam tape with grey color, it utilizes the viscoelasticity of acrylic foam as backing and adhesive at the same time.

Product benefits:

- Sufficient bonding on different substrates
- Good shear resistant
- Temperature resistant

### Main Application

Example mounting applications include but are not limited to:

- Control panel in elevator
- Touch panel in home appliance

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	foamed acrylic	• Elongation at break	890 %
• Color	gray	• Tensile strength	2.6 N/cm
• Total thickness	400 µm	• Type of liner	bi-siliconised paper
• Type of adhesive	pure acrylic		

#### Properties

- |                           |       |                                   |       |
|---------------------------|-------|-----------------------------------|-------|
| • Static shear resistance | ● ● ● | • Static shear resistance at 70°C | ● ● ● |
|---------------------------|-------|-----------------------------------|-------|

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

#### Additional Information

Liner variants:

PV43 White paper with blue logo, d/s release coating (150µm)

# tesa® 6700 New Bond

## Product Information



tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=06700>