

tesa Automotive

Acrylic Foam Tapes – OEM Approvals (July 2022)

	Specifications / Application	tesa® 778XX	tesa® 777XX	tesa® 776XX	tesa® 771XX	tesa® 78XX	tesa® 772XX	tesa® 883XX
Audi	VW TL52018 E	●				●	●	
AvtoVAZ	Part test					●		
BAIC	Material approval					●	●	
BMW	PV 03021	●				●		
	GS 97109	●		●				
BYD	QBYDQ-A1909+0054	●		●		●		
Byton	Part test			●				
Chery	Q/SQR S1-71-2014	●		●		●	●	
Daimler	DBL 7906.30				●	●		
DPCA	B14 1835					●	●	
FAW	Part test			●				
FCA	MS. 90152 Type B, C	●	●	●	●	●		
Ford	WSS-M11P65-A2	●		●	●	●		
Geely	QJLY J7110540A-2012	●		●	●	●	●	
GM	GMW15201 type XVII					●		
GWM	Material / Part approval				●	●		
Hyundai	MS 711-10	●				●		
JLR	STJLR.51.5183.i1.c3	●				●		
MAN	MAN Norm 262-1					●		
Nissan	NES-M 8506				●			
OPEL	GMW15201, 15851, 14650					●		
Porsche	PTL4044					●		
PSA	Part test					●		
Renault	Renault 39-09-005				●			
SAIC	SMTC 5310026			●	●	●	●	
SEAT	VW TL 52018-E	●				●	●	
SGMW	Part test					●	●	
Skoda	VW TL 52018-E					●	●	
Subaru	TS420-06-021					●		
Toyota	TSK5705G							●
Volvo	Part test	●				●		
VW	VW TL 52018-E	●	●	●	●	●	●	

● OEM official material approval obtained

● Successful part approval

● Passed internal test according to customer request

Note: cells without dots mean testing is ongoing or to be initiated

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa Automotive

PE Foam Tapes – OEM / OES Approvals (July 2022)

	Specifications / Application	tesa® 649XX	tesa® 628XX	tesa® 627XX	tesa® 6293X	tesa® 6290X	tesa® 625XX	tesa® 661XX
Audi	TL 52018 Cat 'D'	●	●	●	●	●		
BAIC Group	Locator pins on glass		●			●		
BMW	PV 03021			●				
	Mud flap to wheel arch				●			
BYD	Locator pins on glass		●					
Chrysler	MS.90152		●					
Dacia	Mounting of interior lights					●		
Dongfeng	Mirror assembling				●			
Fiat	9.55368 Type A		●	●		●		
Ford	WSS-M11P65-A		●	●		●		
	Mirror assembling						●	
Geely	Q/JLY J711-2012					●		
	Locator pins on glass		●					
GM	GMW 15201 – Type III		●	●			●	
Hyundai	LCD module mounting				●		●	
	Mirror assembling	●					●	
Iveco	IS 18-17111 Type A			●		●		
Jeep	Locator pins on glass		●					
JLR	STJLR.51.5183.i1.c3	●						
Magna	GDS 010.000.001-03 for mirror					●		●
Mercedes	DBL 7906				●			
Plastic	For non-critical attachment part	●						
Omnium	B14 1835		●	●		●		
PSA	39-09-005/F Function I Category III	●	●			●		
Renault	SMTC 5 310 026 Type II			●		●		
SAIC Group	Emblem mounting for Roewe		●					
	TL 52018 Cat 'D'	●	●	●	●	●		
Seat	BT/SGMWJ 0640-2012		●	●				
SGMW	TL 52018 Cat 'D'	●	●	●	●	●		
Skoda	Mirror assembling							
Tesla	NOTE-TREG-1286302-005-01		●				●	
Volvo	TL 52018 Cat 'D'	●	●	●	●	●		

- OEM official material approval obtained
- Successful part approval
- Passed internal test according to customer request

Note: cells without dots mean testing is ongoing or to be initiated

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.