

tesa® Paper Standard – 58291, 58292, 58293

tesa® Paper Standard is a general-purpose packaging tape based on a fine crepe paper backing and a natural rubber adhesive. The paper backing of tesa® Paper Standard is made with paper from well-managed, FSC®-certified forests and other controlled sources. The natural rubber adhesive system features good adhesion to multiple surfaces as well as good tack.



Main Application

- Sealing of light-weight cardboardes
- Good adhesion in recycled cardboards
- Suitable for manual and automatic dispensers
- Recycling-friendly tape according to INGEDE Method



Technical Data & Properties

Dimensions	50 m : 50 mm 3 x 50 m : 50mm 25 m : 38 mm
Color	Brown
Backing	FSC®-certified paper
Type of Adhesive	Natural Rubber
Backing Thickness	94 µm
Total Thickness	125 µm
Adhesion/Steel	2,8 N / cm
Tensile Strength	30 N / cm
Elongation at break	10 %

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Additional Information & Pictures



58291



58292



58293

IBNR´s

IBNR	Description
58291	tesa® Paper Standard 50:50
58292	3x tesa® Paper Standard 50:50
58293	tesa® Paper Standard 25:38

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.