



# tesa<sup>®</sup> 4309 PV1



## Product Information

### Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

### Composición del producto

- |                       |                |                                |        |
|-----------------------|----------------|--------------------------------|--------|
| • Material de soporte | papel crepado  | • De base biológica (por peso) | 53 %   |
| • Tipo de adhesivo    | caucho natural | • Espesor total                | 170 µm |

### Propiedades / Valores de rendimiento

- |                           |         |                    |           |
|---------------------------|---------|--------------------|-----------|
| • Elongación a la ruptura | 12 %    | • Fácil de quitar  | si        |
| • Resistencia a la rotura | 47 N/cm | • Hand tearability | very good |

### Adhesión a los valores

- |                        |          |
|------------------------|----------|
| • Adhesión sobre acero | 3.5 N/cm |
|------------------------|----------|

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=04309>