

51786 Detect Plus

Product Information



Multifunctional splicing tape with integrated inductive detection feature

Descripción del producto

tesa® 51786 EasySplice Detect Plus is a double-sided integrated flying splice tape consisting of an aluminised flat-back paper and an acrylic adhesive. tesa® 51786 EasySplice Detect Plus features especially

Color: Orange

Características

- Very high tack properties
- Very high shear resistance
- Extremely good heat resistance
- Best adhesion on coated and uncoated paper
- Low splice thickness
- Reliable detection of splice position
- Smooth and easy application due to a flexible backing
- Available with one or two splitting strips with paper backing for a smooth opening of the new paper reel without jeopardizing the printing process
- Slit liner for the secure fixation of the top sheet is included
- Aluminised backing for a reliable detection of the splice position is included
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel

Aplicación

tesa® 51786 EasySplice Detect Plus is particularly suitable for:

Flying splices in web printing industry

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

•	Material de soporte	Papel aluminizado	•	Color	naranja/plateado
٠	Espesor total	110 µm			

Propiedades / Valores de rendimiento

•	Elongación a la ruptura	6 %	٠	Caducidad (envase)	12 months
•	Resistencia a la rotura	36 N/cm			



51786 Detect Plus

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit http://l.tesa.com/?ip=51786