



tesa® 51026

Product Information



Cinta de PET tejido resistente a la Abrasion

Descripción del producto

tesa® 51026 es una cinta de tela de alambre PET con un adhesivo base acrílico.

Características principales:

- Alta resistencia térmica 150°C/3000h
- Alta resistencia a la abrasión

Colores: Disponible en negro y naranja.

Características

- High abrasion resistance
- High temperature resistance
- Excellent cable compatibility
- Resistant to aging
- Can withstand environmental influences
- Can be used for manual and automatic application
- Flame retardant
- Fogging-free
- Halogen-free
- Tear-resistant
- Constant unwind force
- Flexible and smooth

Aplicación

tesa® 51026 has been specially designed for bundling and wire protection against abrasion of automotive harnesses. The main application field is the engine compartment of a car, with demanding temperature-related and environmental conditions.

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|------------|-----------------|--------|
| • Material de soporte | PET tejido | • Espesor total | 260 µm |
| • Tipo de adhesivo | acrílico | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51026>



tesa[®] 51026

Product Information

Propiedades / Valores de rendimiento

- | | | | |
|--|----------------------|--|----------------------|
| • Elongación a la ruptura | 40 % | • Fuerza de desbobinado (ancho de rollo > 9mm) | 11 N/roll (30 m/min) |
| • Resistencia a la rotura | 275 N/cm | • Temperature resistance max. | 150 °C |
| • Amortiguación del ruido (LV312) | Class A | • Temperature resistance min. | -40 °C |
| • Fuerza de desbobinado (ancho de rollo > 9mm) | 11 N/roll (30 m/min) | | |

Adhesión a los valores

- Adhesión sobre acero 5.5 N/cm

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 25 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mm
- Applicable for red ring assembly aid

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51026>