



tesa® 51618

Product Information



Cinta de PET fleece isonorizante, mayor flexibilidad

Descripción del producto

Tesa® 51618 es una cinta de arnés de alambre polar de PET con un adhesivo a base de caucho.

Características principales:

- Amortiguación de ruido
- Resistente a la abrasión
- Handtearable

Color: Negro

Características

- Noise damping performance
- Basic abrasion resistant performance
- Flexible and smooth appearance
- Tear resistant for secure bundling of harnesses
- Stable unwind force for constant behavior when applying
- Ageing resistance performance
- Strong adhesion
- Hand-tearable for quick application

Aplicación

tesa® 51618 is designed to provide good noise damping and secure bundling performances on the harness. The tape is mainly applied on harnesses for the passenger compartment. The harness remains flexible after applying the tape.

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|---------------------|-----------------|--------|
| • Material de soporte | Fleece de Poliester | • Espesor total | 250 µm |
| • Tipo de adhesivo | basado en caucho | | |

Propiedades / Valores de rendimiento

- | | | | |
|--|---------------------|--|---------------------|
| • Elongación a la ruptura | 20 % | • Fuerza de desbobinado (ancho de rollo ? 9mm) | 9 N/roll (30 m/min) |
| • Resistencia a la rotura | 37 N/cm | • Temperature resistance max. | 105 °C |
| • Amortiguación del ruido (LV312) | Class C | • Temperature resistance min. | -40 °C |
| • Fuerza de desbobinado (ancho de rollo > 9mm) | 9 N/roll (30 m/min) | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51618>



tesa[®] 51618

Product Information

Adhesión a los valores

- Adhesión sobre acero 3 N/cm

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 15, 25 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51618>