



# 51036

## WH alta abrasion



### Product Information

Manga de doble refuerzo de PET Cloth alta resistencia a la abrasion

### Descripción del producto

Tesa Sleeve® 51036 PV7 es un tejido PET recubierto en los bordes con un adhesivo acrílico avanzado (Triple A®) para aplicaciones longitudinales.

Principales características:

- Alta resistencia a la abrasión 150 ° C / 3000h
- Protección de abrasión excepcionalmente alta
- Alta flexibilidad
- Fácil y longitudinal de la aplicación
- Contacto adhesivo mínimo a los cables
- Diseñado para pequeños arneses " tail tail "

De color negro

### Características

- Superior abrasion resistance
- High temperature resistance
- High flexibility
- Easy and efficient lengthwise application
- Ideal solution for small "pigtail" harnesses
- Excellent cable compatibility
- Ageing-resistant
- Resistant to environmental influences
- Flame-retardant
- Fogging-free
- Halogen-free
- Tear-resistant

### Aplicación

tesa Supersleeve® 51036 PV7 has been developed for bundling wire harness areas subject to exacting requirements for temperature and abrasion resistance as well as harness flexibility. The main application fields are harnesses both in the automotive engine as well as the passenger compartment.

### Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

For latest information on this product please visit <http://l.tesa.com/?ip=51036>



# 51036

## WH alta abrasion

### Product Information

#### Composición del producto

- |                       |                   |                 |        |
|-----------------------|-------------------|-----------------|--------|
| • Material de soporte | PET tejido        | • Espesor total | 485 µm |
| • Tipo de adhesivo    | Acrílico avanzado |                 |        |

#### Propiedades / Valores de rendimiento

- |                               |        |                               |        |
|-------------------------------|--------|-------------------------------|--------|
| • Temperature resistance max. | 150 °C | • Temperature resistance min. | -40 °C |
|-------------------------------|--------|-------------------------------|--------|

#### Adhesión a los valores

- |                        |          |
|------------------------|----------|
| • Adhesión sobre acero | 5.5 N/cm |
|------------------------|----------|

#### Additional Information

Standard widths: 50, 95, 140, 190, 230 mm

Standard lengths: 50 m

For smaller "pig tail" harnesses that are less than 10 mm in diameter

- Standard core diameter: 76 mm

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51036>