



tesa[®] 50607 PV41



Product Information

Cinta doble faz para empalmes

Descripción del producto

tesa[®] 50607 es una cinta doble faz de 120 µm translúcida para empalmes y consta de un papel tissue (tela no tejida) recubierto con adhesivo acrílico.

Características:

- Muy buen tack
- Alta resistencia al cizallamiento
- Resistencia a altas temperaturas
- La formulación especial del adhesivo asegura una buena adherencia, incluso en superficies rugosas como cartón corrugado

Disponible en color blanco

Características

- It has high adhesive coating weight
- It offers an especially high tack for a safe initial bond even on rough and heavy paper grades.
- The special adhesive formulation ensures a secure bond on a variety of paper materials, even at elevated temperatures.

Aplicación

- Splicing of paper (liner and flute) in corrugated board production
- Splicing of paper in newsprint and converting processes
- Splicing of heavy paper and cardboard

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|-----------------|-----------------------|--------|
| • Material de soporte | fibra sin tejer | • Espesor total | 120 µm |
| • Tipo de adhesivo | acrílico | • Color del protector | blanco |
| • Tipo de protector | glassine | | |



tesa[®] 50607 PV41

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50607>