



# tesa<sup>®</sup> 4280 Carton sealing



## Product Information

Cinta de empaque PP

## Descripción del producto

tesa<sup>®</sup> 4280 cinta adhesiva de polipropileno de 25 micras y adhesivo de caucho sintético.

## Características

- The packing tape features easy unwinding, is suitable for manual application, and is compatible with any handheld dispenser.
- The carton sealing tape features a short dwell time before reaching final adhesion power, and is very tacky, allowing for fast and precise positioning during application.
- The packing tape shows excellent adhesive properties on both polar and non-polar surfaces.

## Aplicación

tesa<sup>®</sup> 4280 es usada para sellado manual y automático de cajas.

## Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

## Composición del producto

- |                       |                  |                 |       |
|-----------------------|------------------|-----------------|-------|
| • Material de soporte | film PP          | • Espesor total | 42 µm |
| • Tipo de adhesivo    | caucho sintético |                 |       |

## Propiedades / Valores de rendimiento

- |                           |         |                     |    |
|---------------------------|---------|---------------------|----|
| • Elongación a la ruptura | 145 %   | • Aplicación manual | si |
| • Resistencia a la rotura | 40 N/cm |                     |    |

## Adhesión a los valores

- |                        |          |
|------------------------|----------|
| • Adhesión sobre acero | 4.8 N/cm |
|------------------------|----------|



# tesa<sup>®</sup> 4280

## Carton sealing

Product Information

### Additional Information

Color disponible: transparente.

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04280>