



# 51026 WH sleeve



## Product Information

Manga de PET tejido resistente a la Abrasion para armado de mazos de cables

## Descripción del producto

tesa Sleeve®51026 PV9 es una cinta de tela PET para envolvimiento longitudinal de ramales de cables con adhesivo acrílico.

Características:

- Resistencia a altas temperaturas hasta 150°C/3000h
- Alta resistencia a la abrasión
- Alta flexibilidad
- Aplicación longitudinal fácil y eficiente

Disponibile en color negro y anaranjado

## Características

- High temperature resistance
- High flexibility
- Excellent cable compatibility
- Resistant to ageing
- Resistant to environmental influences
- Flame retardant
- Fogging-free
- Halogen-free
- Tear resistant
- Flexible and smooth

## Aplicación

tesa Sleeve® 51026 PV9 has been developed for bundling wire harness areas subject to exacting requirements for temperature resistance as well as harness flexibility. Main application field is the engine compartment with demanding temperatures and environmental conditions. tesa Sleeve® 51026 PV9 is specifically designed for efficient lengthwise manual application.

## Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

## Composición del producto

- |                       |            |                 |        |
|-----------------------|------------|-----------------|--------|
| • Material de soporte | PET tejido | • Espesor total | 220 µm |
| • Tipo de adhesivo    | acrílico   |                 |        |

For latest information on this product please visit <http://l.tesa.com/?ip=51026>



# 51026

## WH sleeve

### Product Information

#### Propiedades / Valores de rendimiento

- Amortiguación del ruido (LV312) Class A
- Temperature resistance max. 150 °C
- Temperature resistance min. -40 °C

#### Adhesión a los valores

- Adhesión sobre acero 5.5 N/cm

#### Additional Information

Standard widths: 68, 78, 100, 130, 155, 195 mm

Standard lengths: 50 m

- Most combinations of width and length are possible

Also available with customized perforation

- Standard perforation length: 100-940 mm (in increments of 10 mm)
- Further dimensions are available on request

Harness diameter / tesa Sleeve® width recommendation

Ø 13 mm – 16 mm / 78 mm

Ø 16 mm - 23 mm / 100 mm

Ø 23 mm – 33 mm / 130 mm

Ø 33 mm – 41 mm / 155 mm

Ø 41 mm – 54 mm / 195 mm

- Standard core diameter: 76 mm
- " = RAL 2007. Some color fadings can occur under continuous strong heat conditions. A standard for color is not specified

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51026>