



# tesa<sup>®</sup> 54999 PV1

## Product Information

Cinta para remoción de liner

### Descripción del producto

Tesa<sup>®</sup> 54999 PV1 es una cinta de tablero translúcida verde con un respaldo de PET con un adhesivo de silicona y un elevador de dedo blanco.

Características y beneficios incluyen:

- Translucido para una aplicación fácil y segura
- Alta rigidez para una buena trabajabilidad
- Elevador digital para posicionamiento preciso
- tesa<sup>®</sup> 54999 está disponible en un forro PET blanco especial

### Características

- Translucent for an easy and secure application
- High stiffness for good workability
- White finger-lift for accurate positioning
- tesa<sup>®</sup> 54999 is available on a special white PET liner

### Aplicación

- Finger-lift for fast liner removal on roll application and die cuts
- For straight tabbing applications, commonly used for bridging to remove the liner from several pieces of tape and/or die cuts in just one operation

### Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

### Composición del producto

- |                       |                    |                 |        |
|-----------------------|--------------------|-----------------|--------|
| • Material de soporte | PET film           | • Espesor total | 150 µm |
| • Tipo de adhesivo    | basado en silicona | • Color         | verde  |
| • Tipo de protector   | PET film           |                 |        |

### Additional Information

Designed for manual tabbing tape application of royal blue liner of tesa<sup>®</sup> ACX<sup>plus</sup> 78XX PV29 and 778XX PV15.  
Standard dimensions:

- 10x30mm incl. 10mm finger-lift
- 6x30mm incl. 10mm finger-lift

Please refer to “Tips & Tricks for tesa<sup>®</sup> Tabbing Tapes” for application guidance.

For latest information on this product please visit <http://l.tesa.com/?ip=54999>



# tesa<sup>®</sup> 54999 PV1

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=54999>