



51608 PV8



Product Information

Manga de PET fleeces anti-vibración, isonorizante

Descripción del producto

Tesa Sleeve® 51608 PV8 es un forro PET recubierto en los bordes con adhesivo de caucho para aplicación longitudinal.

Principales características:

- Alta flexibilidad
- Amortiguación de ruido
- Fácil y eficiente aplicación longitudinal

De color negro

Características

- High flexibility
- Noise damping
- Easy and efficient lengthwise application
- Adhesive-to-adhesive closure system
- Secure bonding without additional spot wraps
- Strong adhesion
- Ageing-resistant
- Flexible and smooth
- The Sleeve® product construction ensures minimum adhesive contact with the wires to provide maximum harness flexibility and the adhesive-to-adhesive closure system guarantees secure bonding without additional spot wraps.

Aplicación

tesa Sleeve® 51608 PV8 has been developed for bundling passenger compartment wire harness areas subject to high requirements for both noise damping and harness flexibility.

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Composición del producto

- | | | | |
|-----------------------|---------------------|-----------------|--------|
| • Material de soporte | Fleece de Poliester | • Espesor total | 210 µm |
| • Tipo de adhesivo | basado en caucho | | |

Propiedades / Valores de rendimiento

- | | | | |
|-----------------------------------|---------|-------------------------------|--------|
| • Amortiguación del ruido (LV312) | Class C | • Temperature resistance min. | -40 °C |
| • Temperature resistance max. | 105 °C | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51608>



51608

PV8

Product Information

Adhesión a los valores

- Adhesión sobre acero 3 N/cm

Additional Information

Standard widths: 80, 100, 130, 180, 250 mm

Standard lengths: 50 m

- Most combinations of width and length are possible

Also available with customized perforation

- Standard perforation length: 100-940 mm (in increments of 10 mm)
- Further dimensions are available on request

Harness diameter / tesa Sleeve® width recommendation

< Ø 18 mm / 80 mm

Ø 18 mm – 24 mm / 100 mm

Ø 24 mm – 33 mm / 130 mm

Ø 33 mm – 49 mm / 180 mm

Ø 49 mm – 72 mm / 250 mm

- Standard core diameter: 76 mm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51608>