

# tesa® 4182 PVC



## product information

Cinta de PVC soft para armado de mazos de cables

Tesa® 4182 PV2 es una cinta de arnés de hilo de película de PVC con un adhesivo acrílico.

Principales características:

- Resistencia a la temperatura 105 ° C / 3000h
- Flexible
- Handtearable

De color negro

## Main Application

tesa® 4182 PV2 has been particularly developed for efficient bundling of wire harness parts in the automotive passenger compartment.

## Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

### Technical Data

• Material de soporte	film PVC	• Resistencia a la temperatura (3000h)	105 °C
• Espesor total	104 µm	• Resistencia a la abrasión (mandril 10mm)	Class A (acc. to LV312)
• Tipo de adhesivo	acrílico	• Resistencia a la abrasión (mandril 5mm)	Class A (acc. to LV312)
• Elongación a la ruptura	250 %	• Retardante de llama en composite	Class B (acc. to LV312)
• Resistencia a la rotura	25 N/cm	• Fuerza de desbobinado (ancho de rollo > 9mm)	7.5 N/roll (30 m/min)
• Resistencia a la temperatura mínima	-25 °C	• Amortiguación del ruido (decibelios)	Class A (acc. to LV312)

### Adhesion to

- Adhesión sobre acero 1.8 N/cm

### Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 33 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mm

For latest information on this product please visit  
<http://l.tesa.com/?ip=04182>

# tesa® 4182 PVC

## product information



### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=04182>