

# tesa® 54678



## Product Information

### Hole Covering PET tejido , mayor conformabilidad

Tesa® 54678 Los cortes de troquel consisten en tela extruida de polietileno basada en una tela de PET / rayón tejida de 45 mesh que está recubierta con un adhesivo de caucho natural. Los troqueles se suministran en un revestimiento de vidrio amarillo.

### Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

#### Technical Data

• Material de soporte	tejido extruído con PE	• Resistencia a la rotura	50 N/cm
• Espesor total	250 µm	• Resistencia a la temperatura (30 min)	95 °C
• Tipo de adhesivo	caucho natural	• Malla	45 contar por pulgada cuadrada
• Elongación a la ruptura	8 %		

#### Adhesion to

- Adhesión sobre acero 4.2 N/cm

#### Properties

- Se puede cortar con la mano. ●●●●
- Linea nítidas de corte ●●●
- Adecuado para troquelar Si
- Resistencia a la abrasión ●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=54678>