

Sugru by tesa® Mouldable Glue

Product Information



BNR 41282, 41281, 41286, 41234, 41212, 41237, 41235, 41283, 41232, 41236, 41231, 41284, 41285, 41233, 41211, 41287

Product Description

Sugru Mouldable Glue by tesa, the world's first mouldable glue that turns into silicone rubber by itself.

Product Features

- Made for fixing, bonding, repairing, sealing, reinforcing, mounting without drilling, DIY ideas
- No mess: non-runny, non-toxic formula for quick and easy application (indoor & amp; outdoor)
- · Versatile: mouldable, waterproof, heat and cold- resistant, durable, electrically insulating
- Strong: holds up to 2kg on glass, ceramics, wood, metal, plaster, most plastics and some fabrics

Application Fields

- Made for fixing, bonding, repairing, sealing, reinforcing, mounting without drilling, DIY ideas
- No mess: non-runny, non-toxic formula for quick and easy application (indoor & amp; outdoor)
- Versatile: mouldable, waterproof, heat and cold- resistant, durable, electrically insulating
- Strong: holds up to 2kg on glass, ceramics, wood, metal, plaster, most plastics and some fabrics

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Type of adhesive

silicone based

Silicone free

no



Sugru by tesa[®] Mouldable Glue

Product Information

Properties/Performance Values

٠	Abrasion resistance	yes
•	Adhesive strength	High adhesion
•	Humidity resistance	yes
•	Material	Silicone
•	Oil and grease resistance	no
•	Ozone resistance	yes
•	Residue-free removability	yes
•	Reusable	no

- Solvent free
- Suitable for children of 3 years yes of age
- Suitable

٠	Suitable surfaces	Most plastics, Glass,
		Cardboard, Carpets,
		Metal, Marble, Steel,
		Stone, Even wood,
		Tiles, Wooden floors,
		Brick, Acrylic glass,
		Paper, Fabrics,
		Concrete, Wallpaper
•	Temperature resistance	yes
•	UV resistant	yes
•	Washable	yes
•	Waterproof	yes

yes

.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



²age 2 of 2 – as of 08/11/24 – en-US

For latest information on this product please visit http://l.tesa.com/?cp=NaN