

tesa® Professional 4663 Heavy Duty Duct Tape

Product Information

Heavy duty duct tape

Product Description

tesa® 4663 is a premium, extra-strength adhesive duct tape popular among craftsmen due, in particular, to its impressive tear resistance and excellent adhesive strength – even on rough or dirty surfaces. The duct tape comprises a PE-coated fabric substrate in combination with a natural-rubber adhesive mass. Due to its resistance to water, vapour and temperatures, the multifunctional adhesive tape can also be used for challenging indoor and outdoor tasks. The duct tape is also easy to handle as it can be torn along a straight edge by hand.

Application Fields

- Indoor and outdoor applications
- Sealing of pipes and ducts
- Fixing heavy-duty construction such as masonry, concrete, render and wood
- Fastening of construction and protection films
- Closing and packaging

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------------|-------------------|--------|
| • Backing | PE laminated cloth | • Total thickness | 300 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|-----------------------|--------|
| • Elongation at break | 15 % | • Hand tearability | good |
| • Tensile strength | 50 N/cm | • Humidity resistance | good |
| • Abrasion resistance | medium | • Water resistance | medium |
| • Ageing resistance (UV) | good | | |

tesa® Professional 4663 Heavy Duty Duct Tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4663PRO>