

# tesa® Bodyguard 50530 PV7



## Product Information

Temporary protection tape for freshly painted surfaces

## Product Description

tesa Bodyguard® 50530 PV7 is the best protection solution for freshly painted car bodies. Applied after the painting process, tesa Bodyguard® 50530 PV7 provides reliable protection for painted surfaces susceptible to damage.

Due to the good UV-resistance and perfect paint compatibility, tesa Bodyguard® 50530 PV7 is the most reliable way to protect cars during the transportation process.

## Product Features

- Reliable protection
- Secure adhesion also at lower temperatures
- Secure adhesion during transport
- Cost savings as polishing or repair after demasking is eliminated
- Paint protection during outdoor storage up to 12 months
- Easy to apply and remove
- Easy disposal – the product is harmless to health and environment and can be disposed to the household or recycling waste

## Application Fields

- Protection of painted surfaces during the assembly, storage and transportation process

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                   |                   |       |
|--------------------|-------------------|-------------------|-------|
| • Backing          | polyolefinic film | • Total thickness | 79 µm |
| • Type of adhesive | EVA               |                   |       |

## Properties/Performance Values

- |                       |           |                            |          |
|-----------------------|-----------|----------------------------|----------|
| • Tensile strength    | 30 N/cm   | • Suitable for die cutting | yes      |
| • Chemical Resistance | very good | • UV-resistance            | 48 weeks |
| • Easy to remove      | yes       |                            |          |

# tesa® Bodyguard 50530 PV7

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50530PV7>