

tesa® Professional 4369

Easy Cover UV

Product Information

Masking film with special outdoor cloth tape

Product Description

tesa® 4369 is a 2-in-1 solution for safely covering and protecting large surfaces during painting work indoors and outdoors – ready to go in just one, time efficient step! This innovative product is a combination of environmentally-friendly, translucent PE film and a duct tape with a natural rubber adhesive mass. tesa® 4369 also provides strong adhesion on slightly rough surfaces and enables clean, straight edges during painting work. The duct tape is simple to use and can be easily removed up to two weeks after application.

Product Features

- Indoor and outdoor applications
- Masking and protecting of large areas
- For clean, straight paint edges
- For smooth and slightly rough surfaces
- Ideal for covering windows during plastering and painting work

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------------------|-----------|
| • Elongation at break | 10 % | • Material of masking coverage | HDPE |
| • Tensile strength | 65 N/cm | • Suitable for rough surfaces | very good |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 2.5 N/cm |
|---------|----------|

tesa® Professional 4369

Easy Cover UV

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=4369>