

tesa® 65605

Removable (Multi-Use)



product information

tesafix

Cinta de espuma de PE de doble cara re-utilizable de 500 µm con una película de refuerzo

Main Application

tesa® 65605 es especialmente adecuado para clientes que desean montar y desmontar piezas desde y hacia una amplia variedad de superficies.

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Technical Data

• Backing material	espuma PE	• Total thickness	500 µm
• Color	blanco	• Type of adhesive	acrílico

Adhesion to

• Steel (initial)	13.0 N/cm	• Steel (after 14 days)	17.0 N/cm
• Steel (covered side, initial)	2.0 N/cm	• Steel (covered side, after 14 days)	3.0 N/cm
• Aluminium (initial)	13.0 N/cm	• Aluminium (after 14 days)	17.0 N/cm
• Aluminium (covered side, initial)	2.0 N/cm	• Alu (covered side, after 14 days)	3.0 N/cm
• Glass (initial)	13.0 N/cm	• Glass (after 14 days)	17.0 N/cm
• Glass (covered side, initial)	2.0 N/cm	• Glass (covered side, after 14 days)	3.0 N/cm
• PE (initial)	0.9 N/cm	• PE (after 14 days)	3.0 N/cm
• PE (covered side, initial)	0.9 N/cm	• PE (covered side, after 14 days)	0.9 N/cm
• PP (initial)	1.2 N/cm	• PP (after 14 days)	3.5 N/cm
• PP (covered side, initial)	1.0 N/cm	• PP (covered side, after 14 days)	1.0 N/cm
• PVC (initial)	8.0 N/cm	• PVC (after 14 days)	17.0 N/cm
• PVC (covered side, initial)	2.0 N/cm	• PVC (covered side, after 14 days)	3.0 N/cm

Properties

• Temperature resistance short term	80 °C	• Resistance to chemicals	●●●●
• Temperature resistance long term	80 °C	• Softener resistance	●●
• Tack	●●●●	• Static shear resistance at 23°C	●●●●
• Ageing resistance (UV)	●●●●	• Static shear resistance at 40°C	●●●●
• Humidity resistance	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

Liner variants:* PVO brown glassine paper (71 µm)

For latest information on this product please visit
<http://l.tesa.com/?ip=65605>

tesa® 65605

Removable (Multi-Use)

product information



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=65605>