

4244



Product Information

Cinta fineline para enmascarado de diseño

tesa® 4244 PV2 es una cinta de enmascarar de PVC conformable, con adhesivo de caucho natural para enmascarado de rayado en procesos de pintura multicolor; se caracteriza por una alta fuerza de tensión, gran capacidad de elongación y es apropiada para la adhesión en superficies con textura y otras condiciones especiales.

- No se encoge en condiciones de altas temperaturas
- Se adapta a cambios dimensionales en procesos de horneado o secado de pintura
- No se desprende sola y al removerla no deja residuos

Main Application

tesa® 4244 PV0 es adecuado para varios tipos de aplicaciones de enmascaramiento.

Información Técnica: (valores promedio)

Los valores en esta sección son considerados solamente como representativos o típicos y no deben usarse para propósitos específicos.

Technical Data

• Backing material	film PVC	• Fuerza de tensión	27 N/cm
• Espesor total	110 µm	• Temperature resistance	140 °C
• Tipo de adhesivo	caucho natural	• Temperature resistance (PP-EPDM)	140 °C
• Elongación a la ruptura	237 %	• Temperature resistance (paint)	140 °C

Adhesión sobre

- Adhesion to steel 3.7 N/cm

Properties

• Hand tearability	●●●●	• Sharp color edge	●●●●
• Easy to remove	Yes	• Powerwash resistance	●●●●
• Suitable for die cutting	Yes	• Conformability	●●●●
• Paint anchorage	●●●●	• Flame retardant	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

4244

Product Information



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04244>