



# tesa<sup>®</sup> Masking Curves

BNR 56360, 56362, 56364, 56533, 56534

## Product Features

- Enables masking of sharp edges and secure adhesion when stretched
- Super-flexible, even suitable for narrow curves
- Can be used on rough and smooth surfaces
- Residue-free removal for up to 7 days indoors
- Extra-strong adhesion
- Suitable for all paints

## Product Description

tesa<sup>®</sup> Masking Tape Curves is a highly flexible masking tape that offers secure masking even on rough surfaces, irregular shapes, curves and sharp edges.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                       |                    |                |
|--------------------|-----------------------|--------------------|----------------|
| • Total thickness  | 375 µm                | • Type of adhesive | natural rubber |
| • Backing material | slightly-creped paper |                    |                |

## Properties/Performance Values

- |                        |        |                                   |         |
|------------------------|--------|-----------------------------------|---------|
| • Residue free removal | yes    | • Tensibility                     | 58 %    |
| • Area of use          | Indoor | • Tensile strength                | 28 N/cm |
| • Tear resistance      | yes    | • Residue-free removable after... | 7 days  |
|                        |        |                                   | days    |

# tesa<sup>®</sup> Masking Curves

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=56360>