

# tesa® Powerstrips Waterproof Hook, Metal



**Product Information** 

BNR 59707

#### **Product Description**

The self-adhesive tesa Powerstrips Waterproof Hook Metal is a removable bathroom hook combining modern design with the strength to hold weights of up to 2 kg.

#### **Product Features**

- Easy to mount without drilling, screws or nails
- Strong hold of up to 2 kg
- Removable without a trace due to the Powerstrips® Waterproof technology
- Made from stainless steel
- Usable on tiles, glass, etc. in humid rooms or directly in the shower\*
- Especially developed for wet areas (e.g. shower, bathtub etc.)
- Hook reusable with tesa Powerstrips Waterproof

\*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

#### **Application Fields**

How to apply - step-by-step:1. Clean the surface with alcohol or silicone-free glass cleaner

2. Take the included waterproof primer tissue and wipe over the surface for bonding preperation - wait for 10 seconds minimum

- 3. Apply the Powerstrip Waterproof Large strip on the surface press for 5 seconds minimum
- 4. Disengage the base plate of the hook and stick it onto the strip press for 5 seconds minimum
- 5. Let the hook slide down on the base plate until it is locked

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### **Product Construction**

•	Type of adhesive	synthetic rubber	•	Hook shape	Rectangular
•	Holding power up to	2 Kg	•	Silicone free	yes



# tesa® Powerstrips Waterproof Hook, Metal

**Product Information** 

## **Properties/Performance Values**

<ul> <li>Application temperature from</li> <li>Application temperature to</li> <li>Applicationfield</li> <li>Area of use</li> <li>Batteries included</li> </ul>	-15 °C 35 °C Bathroom, Kitchen Indoor no	<ul><li>Ozone resistance</li><li>Residue-free removability</li><li>Reusable</li><li>Reusable with</li></ul>	no yes yes Powerstrips Waterproof Large
<ul> <li>Batteries required</li> <li>Chemical Resistance</li> <li>Hazard material</li> <li>Humidity resistance</li> <li>Humidity sealing</li> </ul>	no no yes yes yes	<ul><li>Solvent free</li><li>Suitable surfaces</li></ul>	yes Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal
<ul><li>Material</li><li>Oil and grease resistance</li></ul>	Stainless steel no	<ul> <li>Temperature resistance</li> <li>Temperature resistance max.</li> <li>Temperature resistance min.</li> <li>UV resistant</li> <li>Water resistance</li> </ul>	yes 35 °C 15 °C no yes

Waterproof

yes

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

