

tesa[®] Powerstrips Self-Adhesive Hooks S, Oval

Product Information

BNR 57533, 58275, 57519, 57543

Product Description

Small self-adhesive plastic bathroom and kitchen hook. Removable fixation to safely hang up anything weighing up to 1 kg. Oval design available in white, chrome, matt-chrome and modern matt black color

Product Features

- Easy to mount without drilling, screws or nails
- Strong hold up to 1kg
- Removable without trace thanks to the Powerstrips technology
- Made from high quality plastic
- Usable on tiles, glass, wood, plastic and a variety of other surfaces*
- Hooks reusable with tesa Powerstrips SMALL
- Completely covered tesa Powerstrip

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials

Application Fields

How to apply - Step by step:1. Clean the surface with alcohol or silicone-free glass cleaner

2. Apply the Powerstrip® Small strip on the surface - press for 5 seconds minimum

- 3. Open the hook and stick the back of the hook onto the strip press for 5 seconds minimum
- 4. Close and snap-lock the hook.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	synthetic rubber	٠	Hook shape	Oval
•	Holding power up to	1 Kg	٠	Silicone free	yes



tesa® Powerstrips Self-Adhesive Hooks S, Oval

Product Information

Properties/Performance Values

 Application temperature from Application temperature to Applicationfield Area of use Batteries included Batteries required Chemical Resistance Hazard material 	+15 °C +35 °C Bathroom, Kitchen Indoor no no no no	 Residue-free removability Reusable Reusable with Solvent free Suitable surfaces 	yes yes Powerstrips Small yes Glazed Tiles, Glass, Even wood, Steel, Acrylic glass, Most plastics, Metal
Humidity sealing	no	Temperature resistance	yes
Material	PS (polystyrene)	 Temperature resistance max. 	35 °C
 Oil and grease resistance 	no	 Temperature resistance min. 	15 °C
Ozone resistance	no	UV resistant	no
		Water resistance	no
		Waterproof	no

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 25/02/24 – en-US