

# tesa® Powerbond Double-Sided Mounting Tape Universal

PE foam

acrylic

no



1150 μm

## **Product Information**

BNR 58565

#### **Product Features**

- · Perfect for light and flat object in the office
- · Ideal for interior use
- Easy to apply

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Total thickness

### **Product Construction**

Type of adhesive

Hazard material

Properties/Performance Values			
<ul><li>Ageing resistance (UV)</li><li>Application temperature from</li><li>Applicationfield</li></ul>	yes -10°C Bedroom, Children's room, Hall, Home,	<ul><li>Residue-free removability</li><li>Reusable</li><li>Suitable surfaces</li></ul>	no no Tiles, Most plastics, Glass, Metal, Steel
	Living room, Office,	<ul> <li>Temperature resistance max.</li> </ul>	40 °C
	Bathroom	<ul> <li>Temperature resistance min.</li> </ul>	10 °C
<ul> <li>Area of use</li> </ul>	Indoor	<ul> <li>UV resistant</li> </ul>	no
<ul> <li>Batteries included</li> </ul>	no	<ul> <li>Waterproof</li> </ul>	no
<ul> <li>Batteries required</li> </ul>	no		
<ul> <li>Chemical Resistance</li> </ul>	no		



# tesa® Powerbond Double-Sided Mounting Tape Universal

**Product Information** 

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

