

# tesa® Adhesive nail canvas for wallpaper and plaster 2kg

# **Product Information**

**BNR 77779** 

# **Product Description**

The adjustable adhesive nail for wallpaper & plaster is ideal for mounting a canvas securely and quickly without drilling. Moreover, it can be taken off without a trace and reused.

### **Product Features**

- · Adjustable adhesive nail for sensitive surfaces
- · Attaching stretcher frames and canvases without drilling
- Holds objects of up to 2kg per nail (4kg for two nails)
- Easy On & Off: no tools, removable without a trace
- · Reusable with a new adhesive strip

# Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## **Product Construction**

•	Type of adhesive	synthetic rubber	•	Holding power up to	2 Kg
•	Holding power of strip up to	2 Kg	•	Silicone free	yes

# Properties/Performance Values

•	Application temperature from	-15 °C	•	Residue-free removability	yes
•	Area of use	Indoor	•	Reusable	yes
•	Batteries included	no	•	Reusable with	Adhesive Strip 1kg
•	Batteries required	no			Wallpaper
•	Chemical Resistance	no	•	Solvent free	yes
•	Hazard material	no	•	Suitable surfaces	Wallpaper, Plaster
•	Humidity resistance	no	•	Temperature resistance max.	35 °C
•	Material	PS (polystyrene)	•	Temperature resistance min.	5 °C
•	Oil and grease resistance	no	•	UV resistant	no
•	Ozone resistance	no	•	Waterproof	no



# tesa® Adhesive nail canvas for wallpaper and plaster 2kg

**Product Information** 

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

