

tesa® Bumperfilm 50560 PV1

Temporary protection tape for exterior plastic components

tesa® Bumperfilm 50560PV1 is the best protection solution mainly for painted but also for unpainted plastic components. Applied after the manufacturing process, tesa® Bumperfilm 50560PV1 provides reliable protection for plastic surfaces susceptible to damage.

Due to the good UV-resistance and perfect paint compatibility tesa® Bumperfilm 50560PV1 is the most reliable way to protect painted plastic components during the transportation process.

Features & benefits:

- Reliable protection
- Secure adhesion during transport
- Cost savings as polishing or repair after demasking is eliminated
- Protection during outdoor storage up to 12 months
- Easy to apply and remove
- Easy disposal - both the film and the adhesive system are environmentally friendly

Main Application

- Protection of plastic components during the assembly, storage and transportation process

Technical Data

▪ Backing material	polyolefinic film	▪ Elongation at break	450 %
▪ Total thickness	52 µm	▪ Tensile strength	22 N/cm
▪ Type of adhesive	PIB	▪ UV-resistance	52 weeks
▪ Adhesion to steel	2 N/cm		

Properties

▪ Easy to remove	yes	▪ Paint compatibility	●●●●
▪ Suitable for die cutting	yes	▪ Resistance to chemicals	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=50560>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.