

tesa® 51134

Surface protection and masking tape

tesa® 51134 is a transparent self-adhesive polyethylene tape with an acrylic adhesive for masking large areas of plastic parts during professional painting processes.

Furthermore tesa® 51134 is an interior protection tape for slightly structured surfaces.

Main Application

- Masking during painting applications
- Protection of various surfaces against dust and damage

Technical Data

▪ Backing material	PE film	▪ Elongation at break	200 %
▪ Total thickness	84 µm	▪ Tensile strength	15 N/cm
▪ Type of adhesive	acrylic	▪ Temperature resistance	90 °C
▪ Adhesion to steel	2.4 N/cm		

Properties

▪ Easy to remove	yes	▪ Flame retardant	● ● ●
▪ Paint anchorage	● ● ● ●		
▪ Powerwash resistance	● ● ●		

Evaluation across relevant tesa® assortment: ● ● ● ● very good ● ● ● good ● ● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=51134>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.